

'EZFEED SILAGE FEEDING SORTED.



The most simple, reliable silage wagon on the market designed for farmers who simply cannot afford downtime and rely solely on silage as the supplementary feed of choice.

5 REASONS WHY EZFEED IS BEST-IN-CLASS

- INDUSTRY 1st** 1 **100% Roller Chains** >> With EzFeed gone are the days of trouble-some link chains and conveyor belts which require constant adjustment, fine-tuning and are often slipping or breaking disrupting your feeding program. EzFeed is the first wagon on the market to run a 100% roller-chain design to overcome this.
- INDUSTRY 1st** 2 **Hungry Boards** >> Virtually indestructible our replacable roto-moulded hungry boards can take a beating from your front-loader without turning to splinters or dinging up your nice new EzFeed silage wagon. Another industry first from Hustler.
- INDUSTRY 1st** 3 **TwinFeed** >> The first silage wagon to feature left or right hand feed discharge for more feeding versatility. And with 5 positions for the discharge floor allows for easy setup when feeding into troughs. Coming soon is an electric in-cab controller option for on the fly feed direction change and hydraulic side-shift
- 4 **Simple operation** >> As the name suggests EzFeed makes feeding silage easier than ever before. As standard only one set of hydraulics is all it takes to connect and power the whole machine and our clever adjustable load-sensing hydraulics takes care of the rest making EzFeed the ideal wagon for low-skilled staff
- 5 **Proven Platform** >> Built utilising our proven Combi wagon platform EzFeed has the toughest axle design on the market by a country mile, large suspension travel, comes scale ready for our industry first FeedLink feed management system which weighs on both the jack/skid and drawbar, impact resistant puck-board floors, toughest bars and more

- + Twin 12,000lb roller chains and strong box section bars on bed floor, elevator and conveyer
- + Covered chains prevent material building up in chains & sprockets increasing service life
- + Strongest 65x35x4 box section bolt on replacable bars on elevator and conveyer
- + Sealed reduction gearbox on bed floor, large direct drive elevator and conveyer
- + Heavy-duty oversized covered drive shafts for strength and to eliminate wrapping
- + All drives running on sealed bearings with trash-shields for long life and reduced greasing
- + Scale ready which weighs when on the jack/skid-foot and attached to the tractor
- + Bolt on replaceable heavy duty steel mudguards for strength
- + Standard with central greasing on axle and difficult to reach bearings
- + Protective guarding and covers for hydraulic valves
- + Access ladder
- + Heavy duty crash bumper bars to protect side discharge
- + Massive 1000mm roller chain/bar discharge for a reliable and even unobstructed flow of material
- + Auto release, removable tailgate to prevent damage if floor is reversed
- + Massive drawbar clearance and swivelling eye as standard for tigher turning and safer operation

Pro tip

Ideal for trough feeding, feeding under a wire, feeding along a fence line to avoid trempling and general pasture feeding



Options

- + Feedlink wireless scale and feed management system
- + Hydraulic brakes
- + Visibility kit (includes safety chains, LED lights, and front and rear Hazard panels)

Models in Range

- + **EzFeed SM110** 11m³ silage wagon, 7 ton load rating, 11/80R15.3 wheels
- + **EzFeed SM130** 13m³ silage wagon, 10 ton load rating, 400/60R15.5 wheels
- + **Larger Sizes Coming Soon** ask a Hustler field consultant for more information



	EZFEED SM110	EZFEED SM130
Length	7000 mm	7050 mm
Width	2800 mm	2800 mm
Height	2575 mm	2710 mm
Loading height	2360 mm	2600 mm
Loose Silage (load-level)	11 m ³	13 m ³
Loose Silage (heaped load)	12 m ³	14 m ³
Maximum Load	7,000 kg	10,000 kg
Standard Tyres	400 / 60 x 15.5 Flotation Grip Tread	400 / 60 x 15.5 Flotation Grip Tread
Axle	Tandem Walking Beam	Tandem Walking Beam
Brakes	Optional 2 wheel braking	Optional 2 wheel braking
Guards	Standard removable HD guards	Standard removable HD guards
Remote greasing	Standard	Standard
Ladder	Optional	Optional
Weigh Scales	Optional Feedlink weighing and feed management system	Optional Feedlink weighing and feed management system
Floors (Bed Floor / Cross Floor)	15mm HD Puck Board / 15mm HD Puck Board	15mm HD Puck Board / 15mm HD Puck Board
Chains (Bed / Elevator / Conveyor)	Twin 12,000lb Roller Chains / Twin 12,000lb Roller Chains / Twin 12,000lb Roller Chains	Twin 12,000lb Roller Chains / Twin 12,000lb Roller Chains / Twin 12,000lb Roller Chains
Feed bars (Bed / Elevator / Conveyor)	65 x 35 RHS / 65 x 35 RHS / 50 x 25 RHS	65 x 35 RHS / 65 x 35 RHS / 50 x 25 RHS
Drive system (Bed / Elevator / Conveyor)	Sealed Reduction Gearbox / Direct Drive / Direct Drive	Sealed Reduction Gearbox / Direct Drive / Direct Drive
Hydraulics required	1 x double acting, 50-60 litres/min, 2250-3000 psi	1 x double acting, 50-60 litres/min, 2250-3000 psi
Conveyor	TwinFeed LH & RH side discharge, 1000mm wide chain/slat	TwinFeed LH & RH side discharge, 1000mm wide chain/slat
Jack	80mm 2 speed screw, with quick adjustment. Designed strong enough for use as quick hitch stand	80mm 2 speed screw, with quick adjustment. Designed strong enough for use as quick hitch stand

**FOUR MORE SIZES COMING SOON >> TO BE ANNOUNCED >>
ASK HUSTLER FIELD CONSULTANT FOR MORE INFO**

