Technical Sheet I 2026

HYDROCONQUEST



L3.779.4.90.6



L888.5

REFERENCE NUMBERS
- L3.779.4.06.6 / L3.779.4.56.6 / L3.779.4.96.6
- L3.779.4.70.6 / L3.779.4.90.6 / L3.779.4.99.6
- L3.788.4.06.6 / L3.788.4.56.6 / L3.788.4.96.6
- L3.788.4.70.6 / L3.788.4.90.6 / L3.788.4.99.6

CALIBRE
- Self-winding mechanical movement
- Exclusive Longines calibre L888.5
- Resistant to magnetic fields (ISO 764), with silicon balance-spring
- 11½ lines, 21 jewels, 25 200 vibrations per hour
- Power reserve: up to 72 hours

FUNCTIONS
- Hours, minutes, seconds
- Date aperture at 3 o'clock

CASES
- Ø 39 mm; thickness 11.70 mm
- Ø 42 mm; thickness 11.70 mm
- Round, stainless steel
- Sapphire crystal with multi-layer anti-reflective coating on both sides
- Unidirectional rotating bezel with blue, black, verdant green, slate grey, luminous blue ceramic insert, count up scale, featuring a SuperLumiNova® filled capsule on the triangle at time "0"
- Screw-in crown
- Brushed screw-down case back, with planisphere and Longines logo engraving
- Distance lug to lug:
  Ø 39 mm: 48.10 mm / Ø 42 mm: 51.20 mm
- Distance between lugs:
  Ø 39 mm: 20 mm / Ø 42 mm: 21 mm

DIALS
- Blue, black, green lacquered polished, 11 applied rhodium-plated indexes with Super-LumiNova® treatment
- Frosted blue sunray, 11 applied rhodium-plated indexes with Super-LumiNova® treatment for ref. L3.779.4.99.6 / L3.788.4.99.6

HANDS
- Rhodium-plated and polished, with Super-LumiNova® treatment

WATER RESISTANCE
- Up to 30 bar (300 metres)

BRACELETS
- Stainless steel with double-folding safety clasp, push-piece opening mechanism; micro-adjustment
- Stainless steel Milanese mesh with double-folding safety clasp, push-piece opening mechanism; micro-adjustment

Longines International Public Relations
publicrelations@longines.com - www.longines.com
Press packs are available at mediacenter.longines.com/

LONGINES

Technical Sheet I 2026

HYDROCONQUEST CORPORATE BOUTIQUE AND E-COMMERCE EXCLUSIVE



L3.779.4.98.6



L888.5

REFERENCE NUMBERS
- L3.779.4.98.6
- L3.788.4.98.6

CALIBRE
- Self-winding mechanical movement
- Exclusive Longines calibre L888.5
- Resistant to magnetic fields (ISO 764), with silicon balance-spring
- 11½ lines, 21 jewels, 25 200 vibrations per hour
- Power reserve: up to 72 hours

FUNCTIONS
- Hours, minutes, seconds
- Date aperture at 3 o'clock

CASES
- Ø 39 mm; thickness 11.70 mm
- Ø 42 mm; thickness 11.70 mm
- Round, stainless steel
- Sapphire crystal with multi-layer anti-reflective coating on both sides
- Unidirectional rotating bezel with blue ceramic insert, count up scale, featuring a SuperLumiNova® filled capsule on the triangle at time "0"
- Screw-in crown
- Brushed screw-down case back, with planisphere and Longines logo engraving
- Distance lug to lug:
  Ø 39 mm: 48.10 mm / Ø 42 mm: 51.20 mm
- Distance between lugs:
  Ø 39 mm: 20 mm / Ø 42 mm: 21 mm

DIAL
- Frosted blue sunray, 11 applied rhodium-plated indexes with Super-LumiNova® treatment

HANDS
- Rhodium plated and polished, with Super-LumiNova® treatment

WATER RESISTANCE
- Up to 30 bar (300 metres)

BRACELET
- Stainless steel with double-folding safety clasp, push-piece opening mechanism; micro-adjustment

Longines International Public Relations
publicrelations@longines.com - www.longines.com
Press packs are available at mediacenter.longines.com/