LONGINES

Technical Sheet I 2026

THE LONGINES MASTER COLLECTION



L2.449.5.89.2



L592.5

REFERENCE NUMBERS
- L2.449.4.87.2 / L2.449.5.87.2 / L2.449.5.89.2
- L2.449.4.73.6 / L2.449.4.87.6

CALIBRE
- Self-winding mechanical movement
- Exclusive Longines calibre L592.5
- Silicon balance-spring
- 8 ¾ lines, 22 jewels, 28 800 vibrations per hour
- Power reserve: up to 45 hours

FUNCTIONS
- Hours, minutes, seconds
- Date aperture at 3 o'clock

CASES
- Ø 30 mm; thickness 9.10 mm
- Round, stainless steel, with 2N yellow cap 200 and 2N 18 ct yellow-gold crown for ref. L2.449.5.87.2
- Round, stainless steel, with 5N rose cap 200 and 5N 18 ct rose-gold crown for ref. L2.449.5.89.2
- Sapphire crystal with multi-layer anti-reflective coating on both sides
- Transparent case back with sapphire crystal
- Distance between lugs: 15 mm

DIALS
- Silver barleycorn
- 11 applied Arabic numerals for ref. L2.449.4.73.6
- White mother-of-pearl, with 11 Top Wesselton diamonds VS-SI 8/8; Ø 1.0-1.05; totalling 0.047 ct for ref. L2.449.4.87.2 / L2.449.4.87.6 / L2.449.5.87.2 / L2.449.5.89.2

HANDS
- Blued steel
- Rhodium plated
- PVD 2N yellow
- PVD 5N rose

WATER RESISTANCE
- Up to 3 bar (30 metres)

BRACELET / STRAPS
- Stainless steel with triple-folding safety clasp and push-piece opening mechanism; micro-adjustment
- Blue or bordeaux alligator leather with triplefolding safety clasp and push-piece opening mechanism; micro-adjustment

Longines International Public Relations
publicrelations@longines.com - www.longines.com
Press packs are available at mediacenter.longines.com/

LONGINES

Technical Sheet I 2026

THE LONGINES MASTER COLLECTION



L2.450.5.89.2



L888.5

REFERENCE NUMBERS
- L2.450.4.87.2 / L2.450.5.87.2 / L2.450.5.89.2
- L2.450.4.73.6 / L2.450.4.87.6

CALIBRE
- Self-winding mechanical movement
- Exclusive Longines calibre L888.5
- Silicon balance-spring
- 11 ½ lines, 21 jewels, 25 200 vibrations per hour
- Power reserve: up to 72 hours

FUNCTIONS
- Hours, minutes, seconds
- Date aperture at 3 o'clock

CASES
- Ø 34 mm; thickness 9.30 mm
- Round, stainless steel, with 2N yellow cap 200 and 2N 18 ct yellow-gold crown for ref. L2.450.5.87.2
- Round, stainless steel, with 5N rose cap 200 and 5N 18 ct rose-gold crown for ref. L2.450.5.89.2
- Sapphire crystal with multi-layer anti-reflective coating on both sides
- Transparent case back with sapphire crystal
- Distance between lugs: 18 mm

DIALS
- Silver barleycorn
- 11 applied Arabic numerals for ref. L2.450.4.73.6
- White mother-of-pearl, with 11 Top Wesselton diamonds VS-SI 8/8; Ø 1.0-1.05; totalling 0.047 ct for ref. L2.450.4.87.2 / L2.450.4.87.6 / L2.450.5.87.2 / L2.450.5.89.2

HANDS
- Blued steel
- Rhodium plated
- PVD 2N yellow
- PVD 5N rose

WATER RESISTANCE
- Up to 3 bar (30 metres)

BRACELET / STRAPS
- Stainless steel with triple-folding safety clasp and push-piece opening mechanism; micro-adjustment
- Blue or bordeaux alligator leather with triplefolding safety clasp and push-piece opening mechanism; micro-adjustment

Longines International Public Relations
publicrelations@longines.com - www.longines.com
Press packs are available at mediacenter.longines.com/

LONGINES

Technical Sheet I 2026

THE LONGINES MASTER COLLECTION



L2.949.4.73.2

REFERENCE NUMBERS
- L2.949.4.73.2 / L2.949.4.93.2
- L2.949.4.73.6 / L2.949.4.93.6

CALIBRE
- Self-winding mechanical movement
- Exclusive Longines calibre L888.5
- Silicon balance-spring
- 11 ½ lines, 21 jewels, 25 200 vibrations per hour
- Power reserve: up to 72 hours

FUNCTIONS
- Hours, minutes, seconds
- Date aperture at 3 o'clock

CASE
- Ø 39 mm; thickness 9.05 mm
- Round, stainless steel
- Sapphire crystal with multi-layer anti-reflective coating on both sides
- Transparent case back with sapphire crystal
- Distance between lugs: 20 mm

DIALS
- Silver, blue barleycorn
- 11 applied Arabic numerals

HANDS
- Blued steel
- Rhodium plated

WATER RESISTANCE
- Up to 3 bar (30 metres)



L888.5

BRACELET / STRAP
- Stainless steel with triple-folding safety clasp and push-piece opening mechanism; micro-adjustment
- Blue alligator leather with triple-folding safety clasp and push-piece opening mechanism; microadjustment

Longines International Public Relations
publicrelations@longines.com - www.longines.com
Press packs are available at mediacenter.longines.com/

LONGINES

Technical Sheet I 2026

THE LONGINES MASTER COLLECTION



L2.950.4.73.2



L888.5

REFERENCE NUMBERS
- L2.950.4.73.2 / L2.950.4.93.2 / L2.950.4.79.2
- L2.950.4.73.6 / L2.950.4.93.6 / L2.950.4.79.6

CALIBRE
- Self-winding mechanical movement
- Exclusive Longines calibre L888.5
- Silicon balance-spring
- 11 ½ lines, 21 jewels, 25 200 vibrations per hour
- Power reserve: up to 72 hours

FUNCTIONS
- Hours, minutes, seconds
- Date aperture at 3 o'clock

CASE
- Ø 41 mm; thickness 9.50 mm
- Round, stainless steel
- Sapphire crystal with multi-layer anti-reflective coating on both sides
- Transparent case back with sapphire crystal
- Distance between lugs: 21 mm

DIALS
- Silver, blue barleycorn
- 11 applied Arabic numerals
- 11 applied Eastern Arabic numerals for ref. L2.950.4.79.2 / L2.950.4.79.6

HANDS
- Blued steel
- Rhodium plated

WATER RESISTANCE
- Up to 3 bar (30 metres)

BRACELET / STRAP
- Stainless steel with triple-folding safety clasp and push-piece opening mechanism; micro-adjustment
- Blue alligator leather with triple-folding safety clasp and push-piece opening mechanism; microadjustment

Longines International Public Relations
publicrelations@longines.com - www.longines.com
Press packs are available at mediacenter.longines.com/