

## LONGINES SPIRIT ZULU TIME 1925



L3.803.5.53.6

### REFERENCE NUMBER

L3.803.5.53.6

### CALIBRE

Self-winding mechanical movement  
Exclusive Longines calibre L844.4  
Officially chronometer-certified by the COSC  
Resistant to magnetic fields (ISO 764), with silicon balance spring  
11½ lines, 21 jewels, 25,200 vibrations per hour  
5N PVD rose-coloured rotor with planisphere and prime meridian engraving.  
Power reserve: up to 72 hours

### FUNCTIONS

Hours, minutes, seconds  
Date aperture at 6 o'clock  
GMT

### CASE

Ø 39 mm; 13.50 mm thick  
Round, stainless steel  
Domed sapphire crystal with multi-layer anti-reflective coating on both sides  
Bidirectional rotating bezel, insert with 5N 18K rose gold cap; engraved numerals, indexes and triangle reference mark  
Steel screw-down crown  
Transparent 6-screw case back and special 1925 – 2025 engraving on the circumference  
Distance between lugs: 21 mm

### DIAL

Matt black  
11 applied rose gold-plated Arabic numerals treated with Super-LumiNova®  
Engraving at 6 o'clock: 1925 – 2025

### HANDS

Rose gold-plated, treated with Super-LumiNova®  
Black GMT hand with rose gold-plated arrow, treated with Super-LumiNova®

### WATER-RESISTANCE

Up to 10 bar (100 metres)

### BRACELET / STRAPS

Stainless steel with double-folding safety clasp and push-piece opening mechanism  
Interchangeable  
Black NATO with pin buckle

## LONGINES SPIRIT ZULU TIME 1925



L3.802.4.50.6

### REFERENCE NUMBER

L3.802.4.50.6  
L3.812.4.50.6

### CALIBRE

Self-winding mechanical movement  
Exclusive Longines calibre L844.4  
Officially chronometer-certified by the COSC  
Resistant to magnetic fields (ISO 764), with silicon balance spring  
11½ lines, 21 jewels, 25,200 vibrations per hour  
Power reserve: up to 72 hours

### FUNCTIONS

Hours, minutes, seconds  
Date aperture at 6 o'clock  
GMT

### CASE

Ø 39 mm; 13.50 mm thick/Ø 42 mm; 14.10 mm thick  
Round, stainless steel  
Domed sapphire crystal with multi-layer anti-reflective coating on both sides  
Bidirectional rotating bezel with two-tone ceramic insert (matt black and intense polished black); lacquered numerals and triangle reference mark treated with Super-LumiNova®  
Steel screw-down crown  
6-screw case back  
Distance between lugs: Ø 39 mm: 21 mm/Ø 42 mm: 22 mm

### DIAL

Matt black  
11 applied rose-gold Arabic numerals treated with Super-LumiNova®  
Engraving at 6 o'clock: 1925 – 2025

### HANDS

Rose gold-plated, treated with Super-LumiNova®  
Black GMT hand with rose gold-plated arrow, treated with Super-LumiNova®

### WATER-RESISTANCE

Up to 10 bar (100 metres)

### BRACELET

Stainless steel with double-folding safety clasp and push-piece opening mechanism  
Interchangeable

## LONGINES SPIRIT ZULU TIME



L3.802.4.60.6

### REFERENCE NUMBERS

L3.802.4.60.6  
L3.812.4.60.6

### CALIBRE

Self-winding mechanical movement  
Exclusive Longines calibre L844.4  
Officially chronometer-certified by the COSC  
Resistant to magnetic fields (ISO 764), with silicon balance spring  
11½ lines, 21 jewels, 25,200 vibrations per hour  
Power reserve: up to 72 hours

### FUNCTIONS

Hours, minutes, seconds  
Date aperture at 6 o'clock  
GMT

### CASES

Ø 39 mm; 13.50 mm thick/Ø 42 mm; 14.10 mm thick  
Round, stainless steel  
Domed sapphire crystal with multi-layer anti-reflective coating on both sides  
Bidirectional rotating bezel with blue ceramic insert, lacquered numerals and triangle reference mark treated with Old Radium Light Super-LumiNova®  
Steel screw-down crown  
6-screw case back  
Distance between lugs: Ø 39 mm: 21 mm/Ø 42 mm: 22 mm

### DIAL

Sanded anthracite  
11 applied yellow gold Arabic numerals treated with Old Radium Light Super-LumiNova®

### HANDS

Yellow gold-plated, treated with Super-LumiNova®  
Black GMT hand with yellow gold-plated arrow, treated with Super-LumiNova®

### WATER-RESISTANCE

Up to 10 bar (100 metres)

### STRAP

Stainless steel with double-folding safety clasp and push-piece opening mechanism  
Interchangeable