



ŠKODA OCTAVIA COMBI

Petrol engines

Technical specifications	1.2 TSI/63 kW	1.0 TSI/85 kW	1.0 TSI/85 kW (A)	1.4 TSI/110 kW	1.4 TSI/110 kW (A)	1.8 TSI/132 kW	1.8 TSI/132 kW (A)
Engine							
Engine type	turbocharged petrol engine, in-line, liquid cooling system, DOHC, transverse in front						
Cylinders	4	3		4			
Displacement [cm ³]	1197	999		1395		1798	
Bore × Stroke [mm × mm]	71.0 × 75.6	74.5 × 76.4		74.5 × 80.0		82.5 × 84.2	
Max. engine performance/revs [kW at rpm]	63/4300-5300	85/5000-5500		110/5000-6000		132/5100-6200	
Max. torque/revs [Nm at rpm]	160/1400-3500	200/2000-3500		250/1500-3500		250/1250-5000	
Compression ratio	10.5 : 1					9.6 : 1	
Emission limit	EU 6						
Fuel injection system	electronically controlled direct injection					electronically controlled combined (direct and port) injection	
Ignition	control unit controlled electronic ignition system						
Lubrication	force-feed lubrication with through-flow oil filter						
Fuel quality	unleaded petrol min. RON 95					unleaded petrol min. RON 95 (91)*	
Transmission							
Wheel drive	front wheel drive						
Clutch	hydraulic single dry clutch disc with membrane spring, asbestos free		two coaxial dry multiple-disk clutch, electro-hydraulically operated	hydraulic single dry clutch disc with membrane spring, asbestos free	two coaxial dry multiple-disk clutch, electro-hydraulically operated	hydraulic single dry clutch disc with membrane spring, asbestos free	two coaxial dry multiple-disk clutch, electro-hydraulically operated
Transmission	manual 5-speed fully synchronized	manual 6-speed fully synchronized	automatic 7-speed, DSG, with Tiptronic manual gear changing	manual 6-speed fully synchronized	automatic 7-speed, DSG, with Tiptronic manual gear changing	manual 6-speed fully synchronized	automatic 7-speed, DSG, with Tiptronic manual gear changing
Transmission ratio	I-3.77 II-1.95 III-1.28 IV-0.88 V-0.67 R-3.18	I-3.77 II-1.95 III-1.28 IV-0.97 V-0.78 VI-0.65 R-3.18	I-3.76 II-2.27 III-1.53 IV-1.12 V-1.18 VI-0.95 VII-0.80 R-4.17	I-3.78 II-2.12 III-1.36 IV-1.03 V-0.86 VI-0.73 R-3.60	I-3.50 II-2.09 III-1.34 IV-0.93 V-0.97 VI-0.78 VII-0.65 R-3.72	I-3.78 II-2.12 III-1.36 IV-1.03 V-0.86 VI-0.73 R-3.60	I-3.76 II-2.27 III-1.53 IV-1.13 V-1.18 VI-0.96 VII-0.80 R-4.17
Axle ratio	3.930	4.056	4.438/3.227 R-4.176	3.647	4.800/3.429 R-4.500	3.647	4.438/3.227 R-4.176



ŠKODA OCTAVIA COMBI

Petrol engines

Technical specifications	1.2 TSI/63 kW	1.0 TSI/85 kW	1.0 TSI/85 kW (A)	1.4 TSI/110 kW	1.4 TSI/110 kW (A)	1.8 TSI/132 kW	1.8 TSI/132 kW (A)
Chassis							
Front axle	MacPherson suspension with lower triangular links and torsion stabiliser						
Rear axle	compound link crank-axle					multi-element axle, with one longitudinal and three transverse links, with torsion stabiliser	
Springs	telescopic shock absorbers with coil springs, in the rear outside the springs						
Braking system	hydraulic dual-diagonal circuit braking system vacuum assisted with Dual Rate system						
Brake - front	disc brakes with inner cooling, with single/piston floating caliper						
Brake - rear	disc brakes						
Parking brake	manual, on rear wheels						
Steering system	direct rack and pinion steering with electro mechanic power steering						
Wheels	6J × 15"				6.5J × 16"		
Tyres	195/65 R15				205/55 R16		
Body							
Body	5 door, two compartment, 5 seater						
Drag coefficient c_w	0.303	0.291		0.303	0.299	0.307	
Outside dimensions							
Length	[mm]	4667					
Width	[mm]	1814					
Height (at kerb weight)	[mm]	1465					
Wheel base	[mm]	2686					2680
Clearance (at kerb weight)	[mm]	141					
Height of the loading sill (at kerb weight)	[mm]	631					
Track front	[mm]	1549			1543		
Track rear	[mm]	1540			1534		1542
Inside dimensions							
Width of front seats	[mm]	1454					
Width of rear seats	[mm]	1449					
Headroom in front seats	[mm]	983					
Headroom in rear seats	[mm]	995					
Storage capacity	[l]	610					
Storage capacity with rear seatback folded down	[l]	1740					



ŠKODA OCTAVIA COMBI

Petrol engines

Technical specifications		1.2 TSI/63 kW	1.0 TSI/85 kW	1.0 TSI/85 kW (A)	1.4 TSI/110 kW	1.4 TSI/110 kW (A)	1.8 TSI/132 kW	1.8 TSI/132 kW (A)
Weights								
Kerb weight – incl. driver**	[kg]	1247	1247	1269	1277	1291	1342	1357
Payload – incl. driver**	[kg]	645					585	
Total weight	[kg]	1817	1817	1839	1847	1861	1852	1867
Max. roof load	[kg]	75						
Max. trailer load w/o brakes	[kg]	620		630		640	660	670
Max. trailer load with brakes – 12%	[kg]	1100	1300		1500		1600	
Max. trailer load with brakes – 8%	[kg]	1300	1500		1800			
Max. nose weight	[kg]	75						
Liquids								
Tank capacity	[l]	50						
Performance/consumption								
Maximum speed	[km/h]	178	201	200	216	216	229	229
Acceleration 0–100 km/h	[s]	12.2	10.1	10.2	8.2	8.3	7.4	7.5
Fuel consumption (1999/100/EC)								
Consumption – urban	[l/100 km]	6.0	5.9	5.6	6.8	6.2	7.6	7.1
Consumption – extra-urban	[l/100 km]	4.1	4.2	4.2	4.4	4.3	5.2	5.0
Consumption – combined	[l/100 km]	4.8	4.8	4.7	5.3	5.0	6.1	5.8
CO ₂ emissions	[g/km]	113	109	106	123	116	140	133
Turning circle diameter	[m]	10.4						

* Using low-octane fuel may affect engine performance.

** Figures apply to basic version, weight of driver 75 kg.