Hyundai INSTER	Standard		Cross
Motor & performance	42 kWh battery	49 kWh battery	49 kWh battery
Electric motor type	Permanent Magnet Synchronous Motor (PMSM)		
Maximum power (PS / kW)	97 / 71.1	115 / 84.5	115 / 84.5
Maximum torque (Nm / rpm)	147 / ~4,600	147 / ~5,400	147 / ~5,400
Battery type	Lithium-ion		
Voltage (V)	266 310 310		
0-100 km/h (sec.)	11.7	10.6	10.6
Top speed (km/h)	140	150	150
All-electric range (WLTP*) (km) 15- / 17-inch wheels / roof basket	327 / 303	370 / 360	360 / 293
Charging time 11 kW charging station, 10-100% (h.)	4:00	4:35	4:35
Charging time 50 kW charging station, 10-80% (h.)	0:55		
Charging time 120 kW charging station, 10-80% (h.)	0:30		
Charging time 350 kW charging station, 10-80% (h.)	0:30		
O a manufacture	40 134/6 1 44	AO LAMIL II AAA AAA	AO IMB bashama
Consumption	42 kWh battery	49 kWh battery	49 kWh battery
Fuel consumption combined WLTP (kWh/100 km)*	14.3 (15")	14.9 (15") / 15.1 (17")	15.1 (17") / 18.8 (roof basket)
high-low			
Chassis			
Front suspension	Macpherson		
Rear suspension	СТВА		
Steering type	Column-Type Electric Power Steering (C-MDPS)		
Steering wheel lock to lock turns	2.58		
Turning radius (m)	5.3		
Front brakes	Ventilated disc, floating-caliper with pads wear warning devices (15-inch)		
Rear brakes	Solid disc, floating caliper with pads wear warning device (14-inch)		
ABS	ABS/ESC STD		
Wheels	5.5Jx15-inch / 6.5Jx17-inch		
Tyres	185/65R15 / 205/45R17		
Weight	42 kWh battery	49 kWh battery	49 kWh battery
Curb weight (kg) <i>lightest - heaviest</i>	4-seater: 1,305 - 1,393	4-seater: 1,335 - 1,423	4-seater: 1,358 - 1,453
Payload (kg) lightest - heaviest	4-seater: 337 - 425	4-seater: 322-410	4-seater: 337 -432
Gross vehicle weight (kg)	4-seater: 1,730	4-seater: 1,745	4-seater: 1,790
Load per axle (kg) front / rear	4-seater: 980 / 920	4-seater: 980 / 920	4-seater: 995 / 920
Roof rack load (kg)	100		

Hyundai INSTER	Standard	Cross		
Dimensions exterior				
Overall length (mm)	3,825	3,845		
Overall width (mm)	1,610			
Overall height (mm) / with roof rack / with sharkfin antenna / with roof basket	1,575 / 1,610 /1,614 / 1,715			
Wheelbase (mm)	2,580			
Wheel tread front (mm) 15- / 17-inch wheels	1,414 / 1,402			
Wheel tread rear (mm) 15- / 17-inch wheels	1,425 / 1, 413			
Front overhang / rear overhang (mm)	710 / 535	730 / 535		
Ground clearance (mm)	153			
Dimensions interior				
Headroom front / rear (mm) (with sunroof)	1,028 (987) / 982			
Legroom 1st/ 2nd row (mm)	1,050 / 885			
Shoulder 1st/ 2nd row (mm)	1,290 / 1,260			
Luggage capacity VDA [I] - seats up / sliding seat	280 / 238-351			
Luggage capacity VDA [I] - seats down	1,059			

Notes

Technical specifications listed in this document may vary depending on region and trim.

^{*} The specified fuel consumption and emission data have been determined according to the Worldwide Harmonized Light Vehicles Test Procedure (WLTP). When figures are specified as value ranges, these do not refer to a particular individual vehicle, but to different trims.